


# Curaflex® 6000

 PRESSING WATER

- Cut-out for duct systems
- Use in **unfinished structures**
- For use with **tanking membranes** or **thick coating** (black tank)
- With **fixed and loose flange**
- For **high static load capacity**



**25**  
Years  
Guarantee

## PRODUCT ADVANTAGES

- Optimally designed inner wall for holding the DOYMA sealing systems and building services duct system
- Steel pipe sleeve for high static loads with integrated fixed and loose flange (loose flange split)
- For flush mounting into the formwork

## TECHNICAL DETAILS

- With flanges in accordance with DIN 18533
- Gas and watertight
- Radon proof – according to FHRK information sheet MB101
- Depending on the tanking membrane, installed with packings (1775) arranged on both sides where there is thin and hard film, or accessories where there is a thick coating (1776): sanding of the contact surfaces of the fixed/loose flange

## MATERIAL

- Steel, GGV triple corrosion protection coating; optionally made of stainless steel 1.4301 (V2A) or 1.4571 / 1.4404 (V4A)

Inner diameter of pipe sleeve $D_1$ [DN in mm]	Outer diameter of fixed flange $D_5$ max. [mm]	Standard lengths $L_1$ [mm]
80	440	300
100	460	300
125	480	300
150	510	300
200	560	300
250	610	300
300	660	300
350	710	as per specifications
400	760	
450	810	
500	860	
600	960	
700	1060	

Further material combinations and dimensions available upon request.



### ACCESSORIES (OPTIONAL)\*

- packings (1775) for thin, hard films
- Accessories for thick coating
- Punch for thick coating

\* see accessories section

