

# ring closure RRV

Protection against dirt and splash water

- For sealing of annulus spaces
- Installation in pre-installed pipe sleeve or core bore in waterproof concrete (white tank)
- High variability



DOYMA  
GRIP

## PRODUCT ADVANTAGES

- High variability through an elastic adaptation to the existing pipe/cable
- Easy installation
- Ideal for combining with any Curaflex® gasket insert
- Adaptability to the media pipe

## TECHNICAL DETAILS

- Permanent sight closure for core bores and pipe sleeves
- Dust and splash water protection (IP54)
- Can accommodate axial movements
- Manually adaptable to the media pipe
- DN 100 plugged sealing and from 20–63 mm
- DN 200 plugged sealing and from 108–160 mm

## MATERIAL

- DOYMA-Grip (EPDM)

Inner diameter of pipe sleeve/core bore $D_i$ [DN in mm]	Outer diameter of pipe/cable $d$ [mm]	Article number
100 (99 – 104)	1 x 20 – 31 2 x 5 2 x 7	1 18 5 000 100 0 0
	1 x 32 – 45 2 x 5 2 x 7	
	1 x 46 – 63 2 x 5 2 x 7	
200 (199 – 203)	1 x 108 – 135 2 x 5 2 x 7	1 18 5 000 200 0 0
	1 x 136 – 160 2 x 5 2 x 7	

$L_0$  (max. design length) [mm]:  $\leq 85$  mm

