


Quadro-Sicura® ADS

for buildings with basements

 PRESSING WATER

- Single-compartment house lead-in **with sealing on both sides**
- Installation in **pre-installed pipe sleeve** or **core bore in waterproof concrete (white tank)**
- For utilities **gas or water**
- House lead-ins with **larger dimensions**



Quadro-Sicura®
ADS gas



Quadro-Sicura®
ADS water

PRODUCT ADVANTAGES

- Permanently sealed – no need to re-tension later (maintenance-free)

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB101
- House lead-ins combination from Schuck including tear-off protection and anti-twist protection*, as well as pre-assembled gasket inserts
- Extraction and torsion safety in accordance with DVGW VP 601
- Installation optionally in accordance with DIN 18533

Type/version	House lead-ins combination [DN]	Wall thicknesses [mm]	Inner diameter Core bore/pipe sleeve [mm]
Quadro-Sicura® ADS gas/water	50	240–700	99–103
Quadro-Sicura® ADS gas/water	80		149–153
Quadro-Sicura® ADS gas/water	100		199–203
Quadro-Sicura® ADS gas/water	150		249–253

Further dimensions and versions available upon request.

DN of house lead-ins combination
50
80
100
150

HOUSE LEAD-INS

T-MT-1-514-01/2026

Subject to technical changes. Some illustrations include accessories.

The Quadro-Sicura ADS system is excluded from the DOYMA 25-year warranty.