


Quadro-Sicura® E-BP-R Max

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in as a **round version**
- Use in **unfinished structures made of waterproof concrete**
- Building services duct system for **sealing larger pipe/cable dimensions**.

25
Years
Guarantee



PRODUCT ADVANTAGES

- Bend-resistant jacket pipe (ID 100 or ID 150) for compliance with bending radii and simple cable entry
- Pipes and cables can be laid independently from construction progress
- Subsequent replacement of pipes and cables possible (relining)
- Connection sleeve enables extension on the ground side

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB101
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab

PRODUKTKOMPONENTEN

- Plastic pipe sleeve (PVC)
- Protective cover (PE)
- Bend-resistant jacket pipe (PVC)
- Water barrier (EPDM) with clamps (stainless steel)
- connecting sleeves (EPDM) with clamps (stainless steel)
- Height-adjustable ground spike (steel)
- optionally incl. gasket insert Curaflex Nova® Multi
- optionally incl. gasket insert Curaflex Nova® Uno

| Type/version | Plastic pipe sleeve [DN] | Inner diameter Jacket pipe [mm] |
|---------------------------|--------------------------|---------------------------------|
| Quadro-Sicura® E-BP-R Max | 100 | 110 |
| Quadro-Sicura® E-BP-R Max | 150 | 150 |

The minimum bending radii for the media pipes/cables to be installed must be observed.



Curaflex Nova® Multi



Curaflex Nova® Uno



ACCESSORIES – RECOMMENDED

- Mounting set for Curaflex Nova® gasket inserts

| Product | Plastic pipe sleeve [DN] | Length of jacket pipe | Pipe/cable Ø [mm] | Article number |
|---|--------------------------|-----------------------|-------------------|-----------------|
| Quadro-Sicura® E-BP-R Max incl. Curaflex Nova® Multi | 100 | 3 meters | (0 / 20-63) | 2890 100 026 13 |
| | | 6 meters | | 2890 100 026 16 |
| | | 10 meters | | 2890 100 026 11 |
| | | 15 meters | | 2890 100 026 15 |
| | | 25 meters | | 2890 100 026 12 |

| Product | Plastic pipe sleeve [DN] | Length of jacket pipe | Pipe/cable Ø [mm] | Article number |
|---|--------------------------|-----------------------|-------------------|-----------------|
| Quadro-Sicura® E-BP-R Max incl. Curaflex Nova® Uno | 150 | 3 meters | 63-68 | 2890 150 065 13 |
| | | 6 meters | | 2890 150 065 16 |
| | | 10 meters | | 2890 150 065 11 |
| | | 15 meters | | 2890 150 065 15 |
| | | 25 meters | | 2890 150 065 12 |
| | | 3 meters | 73-78 | 2890 150 075 13 |
| | | 6 meters | | 2890 150 075 16 |
| | | 10 meters | | 2890 150 075 11 |
| | | 15 meters | | 2890 150 075 15 |
| | | 25 meters | | 2890 150 075 12 |
| | | 3 meters | 87-92 | 2890 150 090 13 |
| | | 6 meters | | 2890 150 090 16 |
| | | 10 meters | | 2890 150 090 11 |
| | | 15 meters | | 2890 150 090 15 |
| | | 25 meters | | 2890 150 090 12 |

Further dimensions and versions available upon request.

The bend-resistant jacket pipe can alternatively be blue or black in colour depending on availability.

Additional information about our Curaflex® sealing systems can be found in the applicable product documentation.