


# Quadro-Sicura® E-BP/SRB

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in as a **round version**
- Use in **unfinished structures made of waterproof concrete**
- House lead-in for sealing **flexible pre-insulated local and district heating pipes**

25  
years  
guarantee



Quadro-Sicura®  
E-BP/SRB (DN 200)

## PRODUCT ADVANTAGES

- Rigid pipe bend for compliance with bending radii and easy pipe entry
- Pipes and cables can be laid independently from construction progress
- Subsequent replacement of pipes and cables possible (relining)
- Earth-side extension possible with commercially available pipes (plug-in sleeve)

## TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB101
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab
- Cast-in part consisting of plastic pipe sleeve and one connecting sleeve including integrated bend-resistant jacket pipe and height-adjustable rod
- Quadro-Sicura® E-BP/SRB with nominal diameter 200 for pipes and cables with diameters from 75 to 142 mm
- Quadro-Sicura® E-BP/SRB with nominal diameter 250 for pipes and cables with diameters from 141 to 178 mm

Type/version	Plastic pipe sleeve		bending radii pipe bend [mm]
	[DN]	[ID/mm]	
Quadro-Sicura® E-BP/SRB	200	188	800
Quadro-Sicura® E-BP/SRB	250	235	800

The minimum bending radii for the media pipes/cables to be installed must be observed.



- **ACCESSORIES – NECESSARY**
- Curaflex® C40/SRB  
(see selection table on next page)



Quadro-Sicura®  
E-BP/SRB (DN250)



Product	Plastic pipe sleeve		Pipe/cable Ø [mm]	Article number
	DN	ID [mm]		
Quadro-Sicura® E-BP/SRB	200	188	75 - 142	2850 000 200 00
	250	235	141 - 178	2850 000 250 00

Product	Plastic pipe sleeve		Pipe/cable Ø [mm]	Article number
	DN	ID [mm]		
Curaflex® C 40/SRB	200	188	75 - 80	1034 075 188 00
			88 - 93	1034 090 188 00
			109 - 114	1034 110 188 00
			123 - 128	1034 125 188 00
			138 - 142	1034 140 188 00
	250	235	141 - 146	1034 142 235 00
			158 - 163	1034 160 235 00
			173 - 178	1034 175 235 00

Further dimensions and versions available upon request.

Additional information about our Curaflex® sealing systems can be found in the applicable product documentation.



Curaflex Nova® C40/SRB