


# Quadro-Sicura® MIS 90

for buildings with basements



- Single-compartment house lead-in with injection system
- Use in the most common wall types with sealing in accordance with DIN 18533 W2.1-E (black tank) or for core bore in waterproof concrete (white tank)
- For all cable types or water lines



25  
Years  
Guarantee

## PRODUCT ADVANTAGES

- Allows for the simultaneous routing of electricity or water and telecommunications
- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

## TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon proof – according to FHRK information sheet MB101
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for core bore in waterproof concrete (white tank)

## THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 90
- Wall termination sleeve
- Expansion resin
- Quick-clamping device
- Selectable collar plugs



### ACCESSORIES – RECOMMENDED

- 2K cartridge gun

Supply lines	Line diameters
Water, electricity or telecommunications	1 × 24–40 mm or 3 × 7–12 mm or 1 × 24–52 mm or 1 × 14–21 mm or 3 × 7–13 mm or 1 × 5–13 mm (Please specify the diameter with your order)
Dimensions	
Core bore/pipe sleeve Ø	92–102 mm
Wall thicknesses	200–900 mm optionally 900–1200 mm

Further dimensions and versions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 90 PU (packaging unit) 6 items	for 1 x (24 – 40 mm) and 3 x (7 – 12 mm)	2120 040 000 00
	for 1 x (24 – 52 mm)	2120 050 000 00
	for 1 x (14 – 21 mm), 3 x (7 – 13 mm) and 1 x (5 – 13 mm)	2120 020 000 00

Including 6 items from the 2K resin system, one quick-clamping device.