


# Quadro-Sicura® O.Con 1

for buildings without basements

 PRESSING WATER

- Single-compartment house outlet with as **version simple**
- Use in **structures yet to be built of WU concrete**
- **House lead-out for all types of cables or water pipes**
- **Ideal for connections in the garden or outdoors**

25  
years  
guarantee



## PRODUCT ADVANTAGES

- Later insertion of pipes for use in garden or outdoor areas. or outdoor areas
- No drilling or the like required on the building for later laying of lines
- Various sealing options for different lines possible
- Quick installation

## TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 0,5 bar
- optional installation according to DIN 18533 possible
- suitable for immediate installation in the floor slab or for later installation in a recess in the floor slab floor slab
- connection possibility of flexible casing pipes DN 75
- End plug is pre-fitted with gas- and pressure-water-tight blanking plugs
- optionally available with 3 m, 6 m, 10 m or 15 m flexible outer casing available
- for pipes  $\varnothing \geq 40$  mm we recommend the use of Quadro-Sicura® E-BP-R Max.

## THE HOUSE LEAD-OUT CONSISTS OF:

- Plastic pipe sleeve incl. blind cover
- Connection sleeve for connecting pipe sleeve/casing pipe
- End plug for sealing the pipe

Quadro-Sicura® O.Con 1	Pipe/cable $\varnothing$ [mm]
XLWL end plug	Outer diameter: 2 x 5-7 mm, 2 x 7-13 mm, 1 x 12-16 mm, 1 x 23-40 mm

Further dimensions and designs on request.



## ACCESSORIES – RECOMMENDED

- flexible casing pipe DN 75
- height-adjustable installation device
- End plug XLWL for ground-side line-sealing
- Sealing sleeve for connection of a sealing membrane



Product	Plastic pipe sleeve [DN]	Length of jacket pipe DN 75	Article number
Quadro-Secura® O.Con 1	75	-	2285 000 000 00
		3 metre	2285 000 000 03
		6 metre	2285 000 000 06
		10 metre	2285 000 000 01
		15 metre	2285 000 000 05

## Accessories

Product	Article number
Height adjustable set-up device (2799)	2990 799 999 00
XLWL end plug for earth-side cable sealing (2704)	2990 704 925 50
Sealing sleeve for connecting a waterproofing membrane to the floor slab (2718)	2990 718 075 00
Flexible casing pipe DN 75, black, 50 metre roll (2775)	2990 775 675 00
Retaining plate for connecting two pipe sleeves	2990 339 814 0 0

Height adjustable  
Set-up device  
(2799)



Retaining plate for  
connecting two pipe sleeves



XLWL end plug (2704)  
for earth-side cable sealing



Sealing sleeve (2718)  
for connecting a waterproofing  
membrane to the floor slab



Flexible casing pipe DN 75  
(2775)

